

View Online at <https://aerobasegroup.com/nsn/5950-00-645-1551>

Reliability Indicator:

Not established

Overall Length:

4.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.938 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.625 inches single mounting facility single center group

Overall Width:

4.375 inches

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Height:

6.312 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

240.0 milliamperes ac single component single secondary

Winding Operating Voltage:

950.00 ac volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

8 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0