NSN 5950-00-645-1730

Vibrator Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-1730

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.625 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.375 inches single mounting facility single center group
Frequency Rating:
60.0 hertz single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
3.562 inches
Body Width:
3.250 inches
Body Height:
4.000 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
2 primary single component and 2 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.190 inches single group
Winding Operating Current:
300.0 milliamperes ac single component 1st secondary
Winding Operating Voltage:
530.00 ac pounds per hour wet single component 2nd secondary
Thread Series Designator:
Unf single group
Terminal Type And Quantity:
10 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5950-00-645-1730

Vibrator Power Transformer - Page 2 of 2



Fiig:

A058b0