## NSN 5950-00-645-1833

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-645-1833

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.031 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.156 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 400.0 hertz single component  |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 1.516 inches  |
| Body Width:   |
| 1.375 inches  |
| Body Height:  |
| 1.500 inches  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component               |
| Thread Size:  |
| 0.112 inches single group   |
| Winding Operating Current:  |
| 1.0 milliamperes ac single component single secondary                     |
| Winding Operating Voltage:  |
| 15.00 ac volts single component single secondary                          |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 4 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

110

Fiig:

A058b0