NSN 5950-00-645-1838

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-645-1838

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.375 inches single mounting facility single center group
Frequency Rating:
50.0 hertz single component and 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
6.656 inches
Body Width:
4.219 inches
Body Height:
6.688 inches
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
2 primary single component and 2 secondary single component
_ ha., aa., ah.aa a.a.a., aa.
Winding Operating Voltage:
Winding Operating Voltage:
Winding Operating Voltage: 110.00 ac pounds per hour wet single component all secondary
Winding Operating Voltage: 110.00 ac pounds per hour wet single component all secondary Terminal Type And Quantity:
Winding Operating Voltage: 110.00 ac pounds per hour wet single component all secondary Terminal Type And Quantity: 8 standoff, threaded stud
Winding Operating Voltage: 110.00 ac pounds per hour wet single component all secondary Terminal Type And Quantity: 8 standoff, threaded stud Shelf Life:
Winding Operating Voltage: 110.00 ac pounds per hour wet single component all secondary Terminal Type And Quantity: 8 standoff, threaded stud Shelf Life: N/a
Winding Operating Voltage: 110.00 ac pounds per hour wet single component all secondary Terminal Type And Quantity: 8 standoff, threaded stud Shelf Life: N/a
Winding Operating Voltage: 110.00 ac pounds per hour wet single component all secondary Terminal Type And Quantity: 8 standoff, threaded stud Shelf Life: N/a Unit Of Measure:
Winding Operating Voltage: 110.00 ac pounds per hour wet single component all secondary Terminal Type And Quantity: 8 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization:
Winding Operating Voltage: 110.00 ac pounds per hour wet single component all secondary Terminal Type And Quantity: 8 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No