Audio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-1919

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.438 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 2.188 inches single mounting facility single center group                 |
| Impedance Rating In Ohms:   |
| 6000.0 single component single primary                                    |
| Frequency Rating:   |
| 300.0 hertz single component and 15.0 kilohertz single component          |
| Maximum Transformer Power Rating:   |
| 20.0 watts single component   |
| Primary To Secondary Turn Ratio:  |
| 1 to 1 to 1-4/10 single component   |
| Body Length:  |
| 3.250 inches  |
| Body Width:   |
| 3.000 inches  |
| Body Height:  |
| 3.719 inches  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 2 secondary single component               |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.190 inches single group   |
| Winding Operating Current:  |
| 70.0 milliamperes dc single component single primary                      |
| Thread Series Designator:   |
| Unf single group  |
| Terminal Type And Quantity:   |
| 8 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
|   |

Audio Frequency Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

