Audio Frequency Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-645-2029

Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 2.250 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.250 inches single mounting facility single center group Impedance Rating In Ohms: 11400.0 single component single primary Frequency Rating: 400.0 hertz single component and 3.0 kilohertz single component Body Length: 6.000 inches Body Width: 5.750 inches Body Height: 8.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Facility Quantity: 1 primary single component and 1 secondary single component Winding Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A058b0	Reliability Indicator:
2.250 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.250 inches single mounting facility single center group Impedance Rating In Ohms: 11400.0 single component single primary Frequency Rating: 400.0 hertz single component and 3.0 kilohertz single component Body Length: 6.000 inches Body Width: 5.750 inches Body Height: 8.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit of Measure: Demilitarization: No Fig:	Not established
Center To Center Distance Between Mounting Facilities Parallel To Width: 2.250 inches single mounting facility single center group Impedance Rating In Ohms: 11400.0 single component single primary Frequency Rating: 400.0 hertz single component and 3.0 kilohertz single component Body Length: 6.000 inches Body Width: 5.750 inches Body Height: 8.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Sheff Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Center To Center Distance Between Mounting Facilities Parallel To Length:
2.250 inches single mounting facility single center group Impedance Rating In Ohms: 11400.0 single component single primary Frequency Rating: 400.0 hertz single component and 3.0 kilohertz single component Body Length: 6.000 inches Body Width: 5.750 inches Body Height: 8.500 inches Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Sheff Life: Na Unit Of Measure: Demilitarization: No Fig:	2.250 inches single mounting facility single center group
Impedance Rating In Ohms: 11400.0 single component single primary Frequency Rating: 400.0 hertz single component and 3.0 kilohertz single component Body Length: 6.000 inches Body Width: 5.750 inches Body Height: 8.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Center To Center Distance Between Mounting Facilities Parallel To Width:
11400.0 single component single primary Frequency Rating: 400.0 hertz single component and 3.0 kilohertz single component Body Length: 6.000 inches Body Width: 5.750 inches Body Height: 8.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	2.250 inches single mounting facility single center group
Frequency Rating: 400.0 hertz single component and 3.0 kilohertz single component Body Length: 6.000 inches Body Width: 5.750 inches Body Height: 8.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Impedance Rating In Ohms:
400.0 hertz single component and 3.0 kilohertz single component Body Length: 6.000 inches Body Width: 5.750 inches Body Height: 8.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	11400.0 single component single primary
Body Length: 6.000 inches Body Width: 5.750 inches Body Height: 8.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Frequency Rating:
6.00 inches Body Width: 5.750 inches Body Height: 8.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	400.0 hertz single component and 3.0 kilohertz single component
Body Width: 5.750 inches Body Height: 8.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
5.750 inches Body Height: 8.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	6.000 inches
Body Height: 8.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Width:
 8.500 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: 	5.750 inches
Inclosure Type: Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Height:
Hermetically sealed Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	8.500 inches
Mounting Facility Quantity: 6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inclosure Type:
6 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Hermetically sealed
Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Mounting Facility Quantity:
Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No	6 single group
Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Mounting Method:
1 primary single component and 1 secondary single component Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Unthreaded hole single group
Winding Operating Current: 350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Winding Function And Quantity:
350.0 milliamperes dc single component single secondary Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1 primary single component and 1 secondary single component
Terminal Type And Quantity: 5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Winding Operating Current:
5 standoff, threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	350.0 milliamperes dc single component single secondary
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	5 standoff, threaded stud
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A058b0	Fiig:
	A058b0