## NSN 5950-00-645-2224

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-2224
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
5.125 inches single mounting facility single center group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
7.375 inches
Body Width:
5.625 inches
Body Height:
6.125 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
18 single group
Thread Size:
0.312 inches single group
Winding Operating Current:
700.0 milliamperes ac single component single secondary
Winding Operating Voltage:
185.00 ac volts single component single secondary and 825.00 ac volts single component single secondary and 1.01 ac kilovolts single
component single secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
8 standoff insulator
Shelf Life:
N/a

-

**Unit Of Measure:** 

## NSN 5950-00-645-2224

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0