NSN 5950-00-645-2236

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-2236

Reliability Indicator: Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

57.0 hertz single component and 68.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.688 inches

Body Width:

4.937 inches

Body Height:

4.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

84.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

890.00 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-00-645-2236

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0