## NSN 5950-00-645-2242

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-2242
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.438 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.750 inches single mounting facility single center group
Inductance Type:
Swinging
Inductance Rating:
2.30 henry single component single winding and 18.00 henry single component single winding
Frequency Rating:
60.0 hertz single component
Body Length:
4.125 inches
Body Width:
3.438 inches
Body Height:
5.000 inches
Maximum Operating Temp:
95.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Rating Method:
Electrical single component single winding
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.164 inches single group
Winding Operating Current:
30.0 milliamperes dc single component single winding and 275.0 milliamperes dc single component single winding
Dc Resistance Rating In Ohms:
30.000 single component single winding
Thread Series Designator:
Unc single group

2 tab, solder lug

**Terminal Type And Quantity:** 

## NSN 5950-00-645-2242

Reactor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0