## NSN 5950-00-645-2968

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-2968

3
Reliability Indicator:
Not established
Turn Quantity:
19 single component single primary
Inductance Rating:
2.80 microhenries single component single secondary
Frequency Rating:
8.0 megahertz single component
Coil Form Type:
Hollow single component
Adjustment Device Drive Type:
Slotted screw single component
Body Length:
2.219 inches
Body Outside Diameter:
0.938 inches
Overall Diameter:
1.068 inches
Distance Between Mounting Facility Centers:
1.000 inches single mounting facility single center group
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded stud single group
Rating Method:
Winding turns single component single primary and electrical single component single primary
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
40 single group
Thread Size:
0.112 inches single group
Winding Conductor Size:

0.00795 inches american wire gage single component single primary

### **Adjustment Method And Quantity:**

2 adjustable core single component

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

4 turret

# NSN 5950-00-645-2968

Radio Frequency Transformer - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0