## NSN 5950-00-645-2991

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-2991

| Reliability Indicator:  |
|---|
| •   |
| Not established  Turn Quantitus   |
| Turn Quantity:  |
| 676 single component single primary   |
| Inductance Rating:  |
| 350.00 microhenries single component single primary and 4.68 millihenries single component single primary |
| Frequency Rating:   |
| 160.0 kilohertz single component and 180.0 kilohertz single component                                     |
| Coil Form Type:   |
| Solid single component  |
| Body Length:  |
| 2.781 inches  |
| Body Outside Diameter:  |
| 1.719 inches  |
| Distance Between Mounting Facility Centers:   |
| 1.000 inches single mounting facility single center group   |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 2 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Rating Method:  |
| Winding turns single component single primary and electrical single component single primary              |
| Winding Function And Quantity:  |
| 1 primary single component  |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.164 inches single group   |
| Winding Conductor Size:   |
| 0.00315 inches american wire gage single component single primary   |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 3 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <u>-</u>  |
| Demilitarization:   |

No

## NSN 5950-00-645-2991

Radio Frequency Transformer - Page 2 of 2



Fiig:

A058b0