NSN 5950-00-645-3000

3 tab, solder lug

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-3000

Reliability Indicator:
Not established
Turn Quantity:
6000 single component single primary
Inductance Rating:
179.10 millihenries single component single primary and 533.00 millihenries single component single primary
Frequency Rating:
55.0 kilohertz single component
Coil Form Type:
Hollow single component
Adjustment Device Drive Type:
Shaft single component
Body Length:
2.562 inches
Body Width:
2.188 inches
Body Height:
2.500 inches
Distance Between Mounting Facility Centers:
0.875 inches single mounting facility single center group
Inclosure Type:
Open
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded hole single group
Rating Method:
Winding turns single component single primary and electrical single component single primary
Winding Function And Quantity:
1 primary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Conductor Size:
0.00397 inches american wire gage single component single primary
Adjustment Method And Quantity:
1 adjustable core single component
Thread Series Designator:
Unc single group
Terminal Type And Quantity:

NSN 5950-00-645-3000

Radio Frequency Transformer - Page 2 of 2



Sneit	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0