

View Online at <https://aerobasegroup.com/nsn/5950-00-645-3280>

**Reliability Indicator:**

Not established

**Transformer Function:**

Interstage

**Inductance Rating:**

4.05 microhenries single component single primary and 7.20 microhenries single component single primary

**Frequency Rating:**

70.0 kilohertz single component and 250.0 kilohertz single component

**Adjustment Device Drive Type:**

Slotted screw single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

1.880 inches

**Body Width:**

0.938 inches

**Body Height:**

1.906 inches

**Distance Between Mounting Facility Centers:**

0.625 inches single mounting facility single center group

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded stud single group

**Rating Method:**

Electrical single component single secondary

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.138 inches single group

**Adjustment Method And Quantity:**

2 adjustable core single component

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0