

View Online at <https://aerobasegroup.com/nsn/5950-00-645-3386>

Reliability Indicator:

Not established

Impedance Rating In Ohms:

62.5 single component single secondary and 150.0 single component single secondary and 250.0 single component single secondary and 600.0 single component single secondary

Frequency Rating:

20.0 hertz single component and 20.0 kilohertz single component

Maximum Transformer Power Rating:

26.0 decibels single component

Primary To Secondary Turn Ratio:

1 to 1 to 5-7/8 single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

1.750 inches

Body Width:

1.438 inches

Body Height:

2.500 inches

Distance Between Mounting Facility Centers:

1.500 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

10.0 milliamperes dc single component all primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0