

View Online at <https://aerobasegroup.com/nsn/5950-00-645-3386>

**Reliability Indicator:**

Not established

**Impedance Rating In Ohms:**

62.5 single component single secondary and 150.0 single component single secondary and 250.0 single component single secondary and 600.0 single component single secondary

**Frequency Rating:**

20.0 hertz single component and 20.0 kilohertz single component

**Maximum Transformer Power Rating:**

26.0 decibels single component

**Primary To Secondary Turn Ratio:**

1 to 1 to 5-7/8 single component

**Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single component

**Body Length:**

1.750 inches

**Body Width:**

1.438 inches

**Body Height:**

2.500 inches

**Distance Between Mounting Facility Centers:**

1.500 inches single mounting facility single center group

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

2 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

10.0 milliamperes dc single component all primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0