

View Online at <https://aerobasegroup.com/nsn/5950-00-645-3574>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.313 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.062 inches single mounting facility single center group

Impedance Rating In Ohms:

0.195 single component single secondary and 0.78 single component single secondary and 3.12 single component single secondary and 12.5 single component single secondary and 50.0 single component single secondary and 200.0 single component single secondary

Frequency Rating:

300.0 hertz single component and 4.0 kilohertz single component

Maximum Transformer Power Rating:

1.0 watts single component

Primary To Secondary Turn Ratio:

4.47 to 1 single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

1.890 inches

Body Width:

1.765 inches

Body Height:

2.156 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

30.0 milliamperes dc single component single primary

Special Features:

One end of secondary internally grounded to case and case used as common for secondary ratings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0