## NSN 5950-00-645-3587

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-3587

| Reliability Indicator:  |
|---|
| Not established   |
| Turn Quantity:  |
| 9500 single component single winding                                      |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.750 inches single mounting facility single center group                 |
| Overall Height:   |
| 5.312 inches  |
| Inductance Type:  |
| Fixed   |
| Inductance Rating:  |
| 36.00 henry single component single winding                               |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Body Length:  |
| 2.719 inches  |
| Body Width:   |
| 2.344 inches  |
| Body Height:  |
| 4.750 inches  |
| Maximum Operating Temp:   |
| 65.0 degrees celsius  |
| Winding Quantity:   |
| 1 single component  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Rating Method:  |
| Electrical single component single winding                                |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.164 inches single group   |
| Winding Operating Current:  |
| 60.0 milliamperes dc single component single winding                      |

Dc Resistance Rating In Ohms:

1240.000 single component single winding

## NSN 5950-00-645-3587

Reactor - Page 2 of 2



| Thread Series Designator:   |
|-----------------------------|
| Unc single group            |
| Terminal Type And Quantity: |
| 3 standoff insulator        |
| Shelf Life:                 |
| N/a                         |
| Unit Of Measure:            |
|                             |
| Demilitarization:           |

No Fiig: A058b0