

View Online at <https://aerobasegroup.com/nsn/5950-00-645-3602>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Mounting Hole Diameter:

0.125 inches single group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.250 inches

Body Width:

3.438 inches

Body Height:

3.906 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

2.0 amperes ac single component single secondary

Winding Operating Voltage:

4.00 ac volts single component single secondary and 8.00 ac volts single component single secondary and 16.00 ac volts single component single secondary and 20.00 ac volts single component single secondary and 24.00 ac volts single component single secondary

Terminal Type And Quantity:

7 threaded stud and 2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0