Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-645-3624

	Reliability Indicator: Not established
	Center To Center Distance Between Mounting Facilities Parallel To Length
	3.312 inches single mounting facility single center group
	Center To Center Distance Between Mounting Facilities Parallel To Width:
	2.688 inches single mounting facility single center group
	Frequency Rating:
	60.0 hertz single component
	nput-output Phase Relationship:
	Single phase to single phase single component
	Vinding Shielding Method:
	External inclosure single component
	Body Length:
	Body Width:
	.688 inches
В	Body Height:
	.500 inches
lr	nclosure Type:
	Hermetically sealed
N	Nounting Facility Quantity:
	single group
	Nounting Method:
т	- Threaded stud single group
W	Vinding Function And Quantity:
1	primary single component and 1 secondary single component
W	Vinding Operating Current:
3	8.18 amperes ac single component single primary input
v	Vinding Power Rating:
	45.0 volts-amperes single component single primary input
	Vinding Operating Voltage:
7	8.00 ac volts single component single primary output
т	erminal Type And Quantity:
3	tab, solder lug
s	Shelf Life:
N	l/a
U	Jnit Of Measure:
	-
D	Demilitarization:
N	lo
F	iig:
A	\058b0