

View Online at <https://aerobasegroup.com/nsn/5950-00-645-3736>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

200.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

500.0 volt-ampere single component

Body Length:

4.750 inches

Body Width:

2.438 inches

Body Height:

3.375 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

2.0 amperes ac single component single secondary

Winding Operating Voltage:

6.00 ac volts single component single secondary and 7.10 ac volts single component single secondary

Special Features:

3 kv insulation test; winding tap location, resonant winding, tap w/o center tap; winding function and qty, resonant winding 1

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0