

View Online at <https://aerobasegroup.com/nsn/5950-00-645-3736>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.500 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.188 inches single group

**Frequency Rating:**

200.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

500.0 volt-ampere single component

**Body Length:**

4.750 inches

**Body Width:**

2.438 inches

**Body Height:**

3.375 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

2.0 amperes ac single component single secondary

**Winding Operating Voltage:**

6.00 ac volts single component single secondary and 7.10 ac volts single component single secondary

**Special Features:**

3 kv insulation test; winding tap location, resonant winding, tap w/o center tap; winding function and qty, resonant winding 1

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0