

View Online at <https://aerobasegroup.com/nsn/5950-00-645-3815>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

4.250 inches

Body Width:

4.000 inches

Body Height:

4.875 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

145.0 milliamperes ac single component single primary and 475.0 milliamperes ac single component single primary

Winding Operating Voltage:

3.15 dc volts single component single primary and 9.45 dc volts single component single primary and 12.60 dc volts single component single primary

Special Features:

Moisture resistance and insulation per specification milt 27 grade 1 class a

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0