# NSN 5950-00-645-4654

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-4654

# **Reliability Indicator:**

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

1.812 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

1.688 inches single mounting facility single center group

#### **Overall Height:**

3.422 inches

#### **Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

#### **Body Length:**

2.500 inches

#### **Body Width:**

2.188 inches

#### **Body Height:**

3.047 inches

# **Maximum Operating Temp:**

85.0 degrees celsius

#### **Inclosure Type:**

Hermetically sealed

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

#### **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

# Thready Qty Per Inch (tpi):

32 single group

# Thread Size:

0.138 inches single group

# **Winding Operating Current:**

2.5 amperes ac single component single secondary

# **Winding Operating Voltage:**

6.30 ac volts single component single secondary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

6 tab, solder lug

# NSN 5950-00-645-4654

Power Transformer - Page 2 of 2



She	lf I	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0