NSN 5950-00-645-4856



| Power Transformer - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5950-00-645-4856 |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 5.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.250 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.000 inches single mounting facility single center group |
| Overall Height: |
| 4.500 inches |
| Overall Width: |
| 3.625 inches |
| Frequency Rating: |
| 49.0 hertz single component and 65.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure single component |
| Body Height: |
| 3.156 inches |
| Inclosure Type: |
| Partially enclosed, double shell |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 2 primary single component and 1 secondary single component |

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

140.0 milliamperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component all primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

NSN 5950-00-645-4856Power Transformer - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

Demilitarization:

No

Fiig:

A058b0