# NSN 5950-00-645-4856



Power Transformer - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5950-00-645-4856
Reliability Indicator:
Not established
Overall Length:
5.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.250 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.000 inches single mounting facility single center group
Overall Height:
4.500 inches
Overall Width:
3.625 inches
Frequency Rating:
49.0 hertz single component and 65.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Height:
3.156 inches
Inclosure Type:
Partially enclosed, double shell
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
2 primary single component and 1 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

#### **Thread Size:**

0.164 inches single group

#### **Winding Operating Current:**

140.0 milliamperes ac single component single secondary

#### **Winding Operating Voltage:**

115.00 ac volts single component all primary

### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

7 tab, solder lug

## Shelf Life:

N/a

# **NSN 5950-00-645-4856**Power Transformer - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

Demilitarization:

No

Fiig:

A058b0