

View Online at <https://aerobasegroup.com/nsn/5950-00-645-4878>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.359 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Mounting Slot Width:

0.085 inches single group

Frequency Rating:

20.0 hertz single component and 25.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

4.125 inches

Body Width:

4.062 inches

Body Height:

3.125 inches

Inclosure Type:

Open

Mounting Facility Quantity:

3 2nd group

Mounting Method:

Flange single group and threaded hole single group and slot single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

96.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

32.50 ac volts single component 2nd secondary

Special Features:

Mtg facilities in two rows, ea spaced 0.750 in.C to c in row, thd holes in one row and slots in other row

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0