NSN 5950-00-645-5100

Power Transformer - Page 1 of 1

A058b0



| View Online at https://aerobasegroup.com/nsn/5950-00-645-5100 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.188 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.531 inches single mounting facility single center group |
| Frequency Rating: |
| 380.0 hertz single component and 1.0 kilohertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to core and brought out to terminal single component |
| Body Length: |
| 2.750 inches |
| Body Width: |
| 2.562 inches |
| Body Height: |
| 2.938 inches |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 6 secondary single component |
| Terminal Type And Quantity: |
| 15 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiia: |