NSN 5950-00-645-5675

Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-645-5675

| View Online at https://aerobasegroup.com/nsn/5950-00-645-5675 |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.125 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.750 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.156 inches single group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 3.312 inches |
| Body Width: |
| 3.875 inches |
| Body Height: |
| 3.500 inches |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary, fixed autotransformer type single component |
| Winding Operating Current: |
| 11.7 amperes ac single component single primary output and 4.87 amperes ac single component single primary output and 680.0 |
| milliamperes ac single component single primary output and 780.0 amperes ac single component single primary output and 326.0 ampere |
| ac single component single primary output |
| Winding Power Rating: |
| 192.0 volts-amperes single component single primary input |
| Winding Operating Voltage: |
| 16.40 ac volts single component single primary output and 32.80 ac volts single component single primary output and 65.60 ac volts single component single primary output and 82.00 ac volts single component single primary output and 98.40 ac volts single component single |
| primary output |
| Terminal Type And Quantity: |
| 8 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No Eiic

Demilitarization: