

View Online at <https://aerobasegroup.com/nsn/5950-00-645-5783>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Overall Height:

4.062 inches

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

8.000 inches

Body Width:

3.625 inches

Body Height:

3.500 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

65.0 milliamperes dc single component 2nd secondary

Winding Power Rating:

21.0 volts-amperes single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0