## NSN 5950-00-645-5866

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-5866

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.428 inches single mounting facility single center group and 2.444 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.054 inches single mounting facility single center group and 2.070 inches single mounting facility single center group

#### Overall Width:

Between 4.452 inches and 4.608 inches

### **Inductance Type:**

Fixed

### **Inductance Rating:**

4.00 henry single component single winding

### Frequency Rating:

60.0 hertz single component

### **Body Length:**

Between 3.188 inches and 3.250 inches

### **Body Width:**

Between 2.688 inches and 2.750 inches

### **Body Height:**

Between 3.906 inches and 3.968 inches

### **Winding Quantity:**

1 single component

### Inclosure Type:

Hermetically sealed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded stud single group

### **Rating Method:**

Electrical single component single winding

### Thready Qty Per Inch (tpi):

32 single group

### **Thread Size:**

0.164 inches single group

### **Winding Operating Current:**

350.0 milliamperes dc single component single winding

### Dc Resistance Rating In Ohms:

55.000 single component single winding

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

2 turret

# NSN 5950-00-645-5866

Reactor - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0