## NSN 5950-00-645-5979

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-5979

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.359 inches single mounting facility single center group and 1.391 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.234 inches single mounting facility single center group and 1.266 inches single mounting facility single center group

#### Overall Width:

Between 2.563 inches and 2.875 inches

### **Inductance Type:**

Fixed

### **Inductance Rating:**

2.70 henry single component single winding

#### Frequency Rating:

60.0 hertz single component

### **Body Length:**

Between 1.813 inches and 1.938 inches

### **Body Width:**

Between 1.687 inches and 1.812 inches

### **Body Height:**

Between 2.250 inches and 2.438 inches

### **Winding Quantity:**

1 single component

### Inclosure Type:

Hermetically sealed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded stud single group

### **Rating Method:**

Electrical single component single winding

### Thready Qty Per Inch (tpi):

32 single group

### **Thread Size:**

0.138 inches single group

### **Winding Operating Current:**

120.0 milliamperes dc single component single winding

### Dc Resistance Rating In Ohms:

150.000 single component single winding

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

2 solder stud

# NSN 5950-00-645-5979

Reactor - Page 2 of 2



She	lf	L	if	е	:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0