

View Online at <https://aerobasegroup.com/nsn/5950-00-645-6324>

Reliability Indicator:

Not established

Transformer Function:

Line

Impedance Rating In Ohms:

135.0 single component 2nd secondary

Frequency Rating:

1.0 kilohertz single component and 150.0 kilohertz single component

Maximum Transformer Power Rating:

42.0 decibels single component

Primary To Secondary Turn Ratio:

1 to 1 to 8-3/4 single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Length:

1.375 inches

Body Width:

0.906 inches

Body Height:

2.000 inches

Distance Between Mounting Facility Centers:

0.625 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Winding Operating Current:

10.0 milliamperes dc single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0