

View Online at <https://aerobasegroup.com/nsn/5950-00-645-6339>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.600 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.520 inches single mounting facility single center group

Impedance Rating In Ohms:

8.0 single component single secondary

Frequency Rating:

300.0 hertz single component and 6.0 kilohertz single component

Maximum Transformer Power Rating:

200.0 milliwatts single component

Primary To Secondary Turn Ratio:

1 to 55-9/10 single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

1.100 inches

Body Outside Diameter:

1.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

56 single group

Thread Size:

0.086 inches single group

Winding Operating Current:

10.0 milliamperes dc single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0