

View Online at <https://aerobasegroup.com/nsn/5950-00-645-6559>

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.812 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group

**Frequency Rating:**

366.0 hertz single component and 455.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

**Body Length:**

3.875 inches

**Body Width:**

3.125 inches

**Body Height:**

4.750 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 5 secondary single component

**Special Features:**

Case metal material, primary winding 117 v rating, secondary windings rated 5 v at 2 amp, 5 v at 2 amp, 6.3 v at 3 amp, 237 v at 230 ma w/center tap, 539 v at 102 ma w/center tap

**Terminal Type And Quantity:**

15 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0