

View Online at <https://aerobasegroup.com/nsn/5950-00-645-6788>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

5.625 inches single mounting facility single center group

Mounting Slot Width:

0.281 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

2.0 kilovolt-ampere single component

Body Length:

6.875 inches

Body Width:

4.156 inches

Body Height:

6.812 inches

Maximum Operating Temp:

55.0 degrees celsius

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

70.0 milliamperes dc single component 4th secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Terminal Type And Quantity:

4 standoff, screw and 6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0