

View Online at <https://aerobasegroup.com/nsn/5950-00-645-7095>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

320.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

8.000 inches

Body Width:

3.000 inches

Body Height:

4.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

3 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

500.0 milliamperes ac single component single secondary

Winding Operating Voltage:

25.00 ac volts single component single secondary and 385.00 ac volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

15 standoff insulator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0