

View Online at <https://aerobasegroup.com/nsn/5950-00-645-7095>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group

**Frequency Rating:**

320.0 hertz single component and 1.0 kilohertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

8.000 inches

**Body Width:**

3.000 inches

**Body Height:**

4.000 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

3 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

500.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

25.00 ac volts single component single secondary and 385.00 ac volts single component single secondary

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

15 standoff insulator

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0