

View Online at <https://aerobasegroup.com/nsn/5950-00-645-7104>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 1.6 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.250 inches

Body Width:

2.312 inches

Body Height:

2.844 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Winding Tap Location (non-core):

Multiple taps w/o center tap single component single primary output

Winding Operating Current:

4.25 amperes ac single component single primary input

Winding Power Rating:

490.0 volts-amperes single component single primary input

Winding Operating Voltage:

97.00 ac pounds per hour wet single component single primary output and 101.00 ac pounds per hour wet single component single primary output and 106.00 ac pounds per hour wet single component single primary output and 109.00 ac pounds per hour wet single component single primary output and 111.00 ac pounds per hour wet single component single primary output and 112.00 ac pounds per hour wet single component single primary output and 113.00 ac pounds per hour wet single component single primary output and 115.00 ac pounds per hour wet single component single primary output and 116.00 ac pounds per hour wet single component single primary output and 117.00 ac pounds per hour wet single component single primary output and 118.00 ac pounds per hour wet single component single primary output and 119.00 ac pounds per hour wet single component single primary output and 121.00 ac pounds per hour wet single component single primary output

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure: