

View Online at <https://aerobasegroup.com/nsn/5950-00-645-7104>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.250 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.750 inches single mounting facility single center group

**Frequency Rating:**

380.0 hertz single component and 1.6 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

2.250 inches

**Body Width:**

2.312 inches

**Body Height:**

2.844 inches

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and unthreaded hole single group

**Winding Function And Quantity:**

1 primary, fixed autotransformer type single component

**Winding Tap Location (non-core):**

Multiple taps w/o center tap single component single primary output

**Winding Operating Current:**

4.25 amperes ac single component single primary input

**Winding Power Rating:**

490.0 volts-amperes single component single primary input

**Winding Operating Voltage:**

97.00 ac pounds per hour wet single component single primary output and 101.00 ac pounds per hour wet single component single primary output and 106.00 ac pounds per hour wet single component single primary output and 109.00 ac pounds per hour wet single component single primary output and 111.00 ac pounds per hour wet single component single primary output and 112.00 ac pounds per hour wet single component single primary output and 113.00 ac pounds per hour wet single component single primary output and 115.00 ac pounds per hour wet single component single primary output and 116.00 ac pounds per hour wet single component single primary output and 117.00 ac pounds per hour wet single component single primary output and 118.00 ac pounds per hour wet single component single primary output and 119.00 ac pounds per hour wet single component single primary output and 121.00 ac pounds per hour wet single component single primary output

**Terminal Type And Quantity:**

14 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**