

View Online at <https://aerobasegroup.com/nsn/5950-00-645-7114>

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.125 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.625 inches single mounting facility single center group

**Frequency Rating:**

57.0 hertz single component and 1.8 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

4.125 inches

**Body Width:**

3.500 inches

**Body Height:**

4.500 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 6 secondary single component

**Thread Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.164 inches single group

**Special Features:**

Zcase metal material, 0.781 in. O/a h of terminals, primary winding 126.5 v rating w/taps at 103.5 v and 115 v, secondary winding rated 6.3 v at 150 ma, 6.3 v at 600 ma, 6.3 v at 900 ma, 6.3 v at 1 amp, 6.3 v at 7.5 amp, and 1.95 kv at 300 ma

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

16 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0