

View Online at <https://aerobasegroup.com/nsn/5950-00-645-7248>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.300 inches single mounting facility single center group

Mounting Hole Diameter:

0.194 inches single group and 0.204 inches single group

Frequency Rating:

380.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

External inclosure single component

Body Length:

7.000 inches

Body Width:

6.500 inches

Body Height:

7.000 inches

Distance Between Mounting Facility Centers:

6.500 inches single mounting facility single center group and 6.000 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

18 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

83.7 milliamperes ac single component single secondary and 91.5 milliamperes ac single component single secondary and 98.5 milliamperes ac single component single secondary and 106.0 milliamperes ac single component single secondary

Winding Power Rating:

1.4 kilovolt-amperes single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Terminal Type And Quantity:

8 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0