

View Online at <https://aerobasegroup.com/nsn/5950-00-645-7258>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.187 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Mounting Slot Width:

0.218 inches single group

Frequency Rating:

380.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.312 inches

Body Width:

2.438 inches

Body Height:

4.125 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

315.0 milliamperes ac single component single secondary

Winding Operating Voltage:

184.00 ac volts single component single primary and 200.00 ac volts single component single primary and 216.00 ac volts single component single primary

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0