

View Online at <https://aerobasegroup.com/nsn/5950-00-645-8477>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group

Overall Height:

6.157 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

3.938 inches

Body Width:

3.378 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Voltage:

4.20 ac volts single component single secondary and 5.60 ac volts single component single secondary and 13.80 ac volts single component single secondary and 15.80 ac volts single component single secondary and 43.00 ac volts single component single secondary and 45.00 ac volts single component single secondary and 70.00 ac volts single component single secondary and 74.00 ac volts single component single secondary and 78.00 ac volts single component single secondary and 80.00 ac volts single component single secondary and 84.00 ac volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

25 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: