

View Online at <https://aerobasegroup.com/nsn/5950-00-645-8480>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.547 inches single mounting facility single center group and 1.577 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.360 inches single mounting facility single center group and 1.390 inches single mounting facility single center group

Overall Height:

Between 2.931 inches and 3.242 inches

Frequency Rating:

580.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 2.116 inches and 2.241 inches

Body Width:

Between 1.976 inches and 2.976 inches

Body Height:

Between 2.493 inches and 2.680 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

1.5 amperes ac single component single secondary

Winding Operating Voltage:

6.30 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0