## NSN 5950-00-645-8616

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-8616

oliobility Indicator
eliability Indicator: ot established
enter To Center Distance Between Mounting Facilities Parallel To Length
250 inches single mounting facility single center group
enter To Center Distance Between Mounting Facilities Parallel To Width:
812 inches single mounting facility single center group
requency Rating:
0.0 hertz single component or 60.0 hertz single component
put-output Phase Relationship:
ngle phase to single phase single component
inding Shielding Method:
ternal shield grounded to inclosure single component
ody Length:
375 inches
ody Width:
812 inches
ody Height:
500 inches
closure Type:
artially enclosed, double shell
ounting Facility Quantity:
single group
ounting Method:
nreaded stud single group
inding Function And Quantity:
primary single component and 4 secondary single component
nready Qty Per Inch (tpi):
2 single group
nread Size:
138 inches single group
inding Operating Current:
00.0 amperes ac single component 1st secondary
inding Operating Voltage:
00 ac volts single component 2nd secondary
nread Series Designator:
nc single group
erminal Type And Quantity:
ł wire lead
nelf Life:
/a
nit Of Measure:

## NSN 5950-00-645-8616

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

