NSN 5950-00-645-8942



| Power Transformer - Page 1 of 2 | AU |
|---|----|
| View Online at https://aerobasegroup.com/nsn/5950-00-645-8942 | |
| Reliability Indicator: | |
| Not established | |
| Overall Length: | |
| 5.080 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | |
| 3.760 inches single mounting facility single center group | |
| Center To Center Distance Between Mounting Facilities Parallel To Width: | |
| 3.000 inches single mounting facility single center group | |
| Overall Height: | |
| 6.700 inches | |
| Overall Width: | |
| 4.320 inches | |
| Frequency Rating: | |
| 50.0 hertz single component or 60.0 hertz single component | |
| Input-output Phase Relationship: | |
| Single phase to single phase single component | |
| Winding Shielding Method: | |
| Internal shield grounded to inclosure and core single component | |
| Body Height: | |
| 5.400 inches | |
| Inclosure Type: | |
| Hermetically sealed | |
| Mounting Facility Quantity: | |
| 4 single group | |
| Mounting Method: | |
| Threaded stud single group | |
| Winding Function And Quantity: | |
| | |

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

60.0 milliamperes dc single component single secondary

Winding Operating Voltage:

2.50 ac kilovolts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 standoff, solder lug

Shelf Life:

N/a

NSN 5950-00-645-8942Power Transformer - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

Demilitarization:

No

Fiig:

A058b0