NSN 5950-00-645-8945

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-8945

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches single mounting facility single center group Frequency Rating: 50.0 hertz single component or 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 3.960 inches Body Width: 2.140 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thread Size: 0.138 inches single group Winding Operating Current: 2.00 ac volts single component single secondary Winding Operating Current: 2.0.0 ac volts single component single secondary	
Center To Center Distance Between Mounting Facilities Parallel To Length: 1.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches single mounting facility single center group Frequency Rating: 50.0 hertz single component or 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 3.960 inches Body Width: 2.140 inches Body Height: 2.140 inches Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Minding Operating Current: 2.0.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Size: 0.138 inches single group Winding Operating Current: 2.0.0 milliamperes ac single component single secondary Winding Operating Current: 2.0.0 milliamperes ac single component single secondary Winding Operating Current: 2.0.0 milliamperes ac single component single secondary Winding Operating Current: 3.0.0 milliamperes ac single component single secondary Winding Operating Current: 3.0.0 milliamperes ac single component single secondary Winding Operating Voltage: 7.0.00 ac volts single component single secondary Hinead Stries Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	Reliability Indicator:
1.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches single mounting facility single center group Frequency Rating: 50.0 hertz single component or 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 3.960 inches Body Width: 2.140 inches Body Height: 2.140 inches Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Minding Operating Current: 2.0.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Size: 0.138 inches single group Winding Operating Current: 2.0.00 ac volts single component single secondary Winding Operating Current: 2.0.00 ac volts single component single secondary Thread Size: 720.00 ac volts single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Hernel Size: 720.00 ac volts single component single secondary Hernel Size: 720.00 ac volts single component single secondary Hinding Operating Voltage: 720.00 ac volts single component single secondary Hernel Size: 720.00 ac volts single component single secondary Fired Size: 720.00 ac volts single component single secondary Fired Size: 720.00 ac volts single component single secondary Fired Size: 720.00 ac volts singl	Not established
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches single mounting facility single center group Frequency Rating: 50.0 hertz single component or 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 3.960 inches Body Width: 2.140 inches Body Height: 2.140 inches Body Height: 2.140 inches Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 1 primary single component and 1 secondary single component Thread hole single group Winding Function And Quantity: 1 primary single component single secondary 2 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0.0 ac volts single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary<	Center To Center Distance Between Mounting Facilities Parallel To Length:
1.500 inches single mounting facility single center group Frequency Rating: 50.0 hertz single component or 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 3.960 inches Body Width: 2.140 inches Body Height: 2.140 inches Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 1 primary single component and 1 secondary single component Thread Size: 0.138 inches single group Minding Operating Current: 2.0 milliamperes ac single component single secondary Minding Operating Voltage: 720.00 ac volts single component single secondary Thread Size: 0.100 milliamperes ac single component single secondary Minding Operating Voltage: 720.00 ac volts single component single secondary Thread Size: 0.100 milliamperes ac single component single secondary Minding Operating Voltage: 720.00 ac volts single component single secondary Minding Group Minding Altity A single group Minding Altity A single group Minding Operating Voltage: 720.00 ac volts single component single secondary A single group Minding Altity A single group Minding Operating Voltage: 720.00 ac volts single component single secondary Minding Altity A single group Minding Altity A singl	1.500 inches single mounting facility single center group
Frequency Rating: 50.0 hertz single component or 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 3.960 inches Body Width: 2.140 inches Body Height: 2.140 inches Body Height: 2.140 inches Monting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Steie Designator: Unc single group Thread Steie Designator: Winding Operating Voltage: 720.00 ac volts single component single secondary	Center To Center Distance Between Mounting Facilities Parallel To Width:
 b.0. hertz single component or 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 3.960 inches Body Width: 2.140 inches Body Height: 2.140 inches Body Height: 2.140 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Tereninal Type And Quantity: 4 tab, solder lug Shieft Life: 	1.500 inches single mounting facility single center group
Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 3.960 inches Body Width: 2.140 inches Body Height: 2.140 inches Body Height: 2.140 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Sheff Life:	Frequency Rating:
Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 3.960 inches Body Width: 2.140 inches Body Height: 2.140 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Empirication And Quantity: 4 tab, solder lug Sheff Life:	50.0 hertz single component or 60.0 hertz single component
Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 3.960 inches Body Width: 2.140 inches Body Height: 2.140 inches Body Height: 2.140 inches Body Height: 2.140 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0.00 ac volts single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	Input-output Phase Relationship:
Internal shield grounded to inclosure and core single component Body Length: 3.960 inches Body Width: 2.140 inches Body Height: 2.140 inches Body Height: 2.140 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Size Designator: Unc single group Thread Size Designator: 4 tab, solder lug Shelf Life:	Single phase to single phase single component
Body Length:3.960 inchesBody Width:2.140 inchesBody Height:2.140 inchesBody Height:2.140 inchesInclosure Type:Hermetically sealedMounting Facility Quantity:4 single groupMounting Method:Threaded hole single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThready Qty Per Inch (tpi):32 single groupThread Size:0.138 inches single groupWinding Operating Current:2.0 on illiamperes ac single component single secondaryWinding Operating Voltage:720.00 ac volts single component single secondaryThread Series Designator:Unc single groupThread Single groupXinding Operating Voltage:4 solder lugShelf Life:	Winding Shielding Method:
 3.960 inches Body Width: 2.140 inches Body Height: 2.140 inches Body Height: 2.140 inches Body Height: 2.140 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: 	Internal shield grounded to inclosure and core single component
Body Width:2.140 inchesBody Height:2.140 inchesBody Inclosure Type:Hermetically sealedMounting Facility Quantity:4 single groupMounting Method:Threaded hole single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThready Qty Per Inch (tpi):32 single groupThread Size:0.138 inches single groupWinding Operating Current:2.0 milliamperes ac single component single secondaryWinding Operating Voltage:720.00 ac volts single component single secondaryThread Series Designator:Unc single groupThread Series Designator:4 tab, solder lugSheff Life:	Body Length:
 2.140 inches Body Height: 2.140 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Size: Unc single group Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: 	3.960 inches
Body Height: 2.140 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	Body Width:
2.140 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	2.140 inches
Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Sheff Life:	Body Height:
Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Unc single group Thread Series Designator: Unc single group Shelf Life:	2.140 inches
Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	Inclosure Type:
4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	Hermetically sealed
Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	Mounting Facility Quantity:
Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Unc single group terminal Type And Quantity: 4 tab, solder lug Shelf Life:	4 single group
Winding Function And Quantity: primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	Mounting Method:
 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: 	Threaded hole single group
Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	Winding Function And Quantity:
32 single group Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	1 primary single component and 1 secondary single component
Thread Size: 0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	Thready Qty Per Inch (tpi):
0.138 inches single group Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	32 single group
 Winding Operating Current: 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: 	Thread Size:
 2.0 milliamperes ac single component single secondary Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: 	0.138 inches single group
Winding Operating Voltage: 720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	Winding Operating Current:
720.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	2.0 milliamperes ac single component single secondary
Thread Series Designator: Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	Winding Operating Voltage:
Unc single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	720.00 ac volts single component single secondary
Terminal Type And Quantity: 4 tab, solder lug Shelf Life:	Thread Series Designator:
4 tab, solder lug Shelf Life:	Unc single group
Shelf Life:	Terminal Type And Quantity:
	4 tab, solder lug
	Shelf Life:
N/a	N/a
Unit Of Measure:	Unit Of Measure:

NSN 5950-00-645-8945

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

