NSN 5950-00-645-8949

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-645-8949

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 2.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.000 inches single mounting facility single center group Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.000 inches Body Width: 3.000 inches Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization:
Center To Center Distance Between Mounting Facilities Parallel To Length: 2.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.000 inches single mounting facility single center group Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.000 inches Body Width: 3.000 inches Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
2.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.000 inches single mounting facility single center group Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.000 inches Body Width: 3.000 inches Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Center To Center Distance Between Mounting Facilities Parallel To Width: 2.000 inches single mounting facility single center group Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.000 inches Body Width: 3.000 inches Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
2.000 inches single mounting facility single center group Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.000 inches Body Width: 3.000 inches Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.000 inches Body Width: 3.000 inches Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.000 inches Body Width: 3.000 inches Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Input-output Phase Relationship: Single phase to single phase single component Body Length: 3.000 inches Body Width: 3.000 inches Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Single phase to single phase single component Body Length: 3.000 inches Body Width: 3.000 inches Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Body Length: 3.000 inches Body Width: 3.000 inches Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
3.000 inches Body Width: 3.000 inches Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Body Width: 3.000 inches Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
3.000 inches Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Body Height: 3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
3.250 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Open Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Mounting Facility Quantity: 4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
4 single group Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Mounting Method: Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Flange and unthreaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Winding Function And Quantity: 1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
1 primary and 1 secondary single component Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Winding Operating Current: 300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
300.0 milliamperes dc single component single secondary Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Winding Operating Voltage: 2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
2.55 ac volts and 117.00 ac volts single component single secondary Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
Terminal Type And Quantity: 5 threaded stud Shelf Life: N/a Unit Of Measure:
5 threaded stud Shelf Life: N/a Unit Of Measure:
Shelf Life: N/a Unit Of Measure:
N/a Unit Of Measure:
Unit Of Measure:

Demilitarization:
Demilitarization:
No
Fiig:
A058b0