## NSN 5950-00-645-9046

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-9046

### Reliability Indicator:

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches single mounting facility single center group

#### Mounting Hole Diameter:

0.187 inches single group

#### **Frequency Rating:**

400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

**Body Length:** 

3.250 inches

Body Width:

#### 3.250 inches

Body Height:

2.250 inches

#### Installation For Which Designed:

Indoor nonportable

#### Inclosure Type:

Open

#### **Mounting Facility Quantity:**

4 single group

**Mounting Method:** 

Flange single group and unthreaded hole single group

#### Winding Function And Quantity:

1 secondary single component

#### Winding Operating Current:

250.0 amperes ac single component single primary

#### Winding Operating Voltage:

200.00 ac pounds per hour with retaining chain single component single primary

#### **Special Features:**

Primary rated but not included

#### **Terminal Type And Quantity:**

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

# **NSN 5950-00-645-9046** Current Transformer - Page 2 of 2

Fiig: A058b0

