

View Online at <https://aerobasegroup.com/nsn/5950-00-645-9065>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.938 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.250 inches single mounting facility single center group

**Frequency Rating:**

57.0 hertz single component and 63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

700.0 volt-ampere single component

**Body Length:**

5.250 inches

**Body Width:**

5.250 inches

**Body Height:**

4.250 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

20 single group

**Thread Size:**

0.250 inches single group

**Winding Operating Current:**

700.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

6.20 ac pounds per hour wet single component single secondary and 6.40 ac pounds per hour wet single component single secondary

**Special Features:**

Case metal material; 1000v insulation test voltage; transformer fixed type

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0